



Description:

Using elliptical motion and interchangeable pre-tensioned panel screens this Tri-flo PTP shakers are capable of separating particles between 34-4000 microns. Tri-flo shakers have proven their reliability over the decades due to their simplicity, functional design and ease of maintenance.

Specifications:

| | | | |
|---------------|--------------------------|----------------------|------------------------|
| Process Rate: | Dependent on screen mesh | Number of screens: | 2 |
| Cut Point: | Dependent on screen mesh | Size of screens: | 2' x 3' |
| Length: | 6' - 6" | Sq. Ft. of screens: | 12 sq. ft. |
| Width: | 3' - 5" | Availble mesh sizes: | 3 - 400 Mesh |
| Height: | 2' - 0" | Volts: | 230/460 v |
| Weight: | 736 LBS. | Hertz: | 50/60 hz |
| | | Horse Power: | .56 |
| | | | XP or Non-XP available |

Components

| | | |
|-----------|------------------------------|-----------|
| 01-01-178 | Vib Motor, BDP 126-4 | |
| 00-00-040 | Deck, 126E PTP Weldment | |
| 03-01-591 | Motor Mount, 123E/126E Weld | |
| 03-00-533 | Skid, 126E Cut Away Weldment | NOT SHOWN |

| | | |
|--|--|--|
| | | |
|--|--|--|